

Teledyne RESON

Hydrophone TC4038

Broad Band Miniature Probe Hydrophone



The TC4038 is a miniature probe hydrophone, specifically designed as a standard reference hydrophone for high frequencies in the range: 100kHz to 500kHz.

The TC4038 provides a flat frequency response and omnidirectional characteristics in the specified frequency range. The sensor element has excellent stability, which ensures reliable sensitivity over long periods of time.

Because of its small size, the TC4038 is an ideal hydrophone for acoustic measurements in near fields.

The sensor element is permanently encapsulated in high density polyurethane to ensure long term reliability. The strain relief and outer jacket of the cable is also made of high density polyurethane.

4038 can be used in sea or fresh water.

4038 can be used as a projector but is not designed for it – do not exceed 25Vrms. Duty cycle need to be low around 1%.

TECHNICAL SPECIFICATIONS

Usable Frequency range:	10kHz - 800kHz
Linear Frequency range:	100 to 500kHz ± 3 dB
Receiving Sensitivity nominal:	-228dB ± 3 dB re 1V/ μ Pa (at 100kHz)
Horizontal Directivity Pattern:	Omnidirectional ± 2 dB (at 100kHz)
Vertical Directivity Pattern:	60° to 120° ± 3 dB (at 100kHz)
Nominal capacitance:	0.5nF (TC4038-1 w 2m of cable) & 1.3nF (TC4038-4 w 10m of cable)
Max. Operating Pressure:	0,2MPa = 2atm
Max. Operating Depth:	20m
Max. Survival Depth:	30m
Equivalent noise:	80dB re 1 μ Pa (with VP1000 Pre-amp \sqrt Hz at 1 kHz)
Max. Sound Pressure:	0,3M Pa
Operating Temperature range:	-2°C to +40°C
Storage Temperature range:	-30°C to +50°C
Leakage Resistance:	>2Gohm
Impedance:	100Mohm (Min. input for min. noise down to 10 kHz lower frequency limit)
Weight in Air:	20grams
Cable (length and type):	2m double shielded low noise FEP. Insulated OD 1,65mm

PRODUCT BENEFITS

- Reference hydrophone for high frequencies
- Linear receiving response from 100kHz to 500kHz
- Individually calibrated
- Calibration as standard reference hydrophone traceable to national standards established at NPL, UK



Hydrophone TC4038

Broad Band Miniature Probe Hydrophone


Documentation:

Receiving sensitivity:
50 kHz to 800 kHz


Horizontal directivity:
250 kHz

Vertical directivity:
250 kHz


Receiving Sensitivity [dB re 1V/μPa @ 1m]




Transmitting Response [dB re 1μPa/V @ 1m]



Horizontal directivity pattern



Vertical directivity pattern



Hydrophone TC4038


Broad Band Miniature Probe Hydrophone

Accessories included:

- BNC to MEMO FFA Adapter: 1 pcs Lemo part No.: ABA 00250 NTL

The calibration as standard reference hydrophones are traceable to national standards established at NPL (available upon request).

Outline Dimensions



For more details visit www.teledyne-reson.com or contact your local Teledyne RESON Office. Teledyne RESON reserves the right to change specifications without notice. 2016@Teledyne RESON

PLD17165-1A

Teledyne RESON A/S

Denmark
Tel: +45 4738 0022
info@teledyne-reson.com

Teledyne RESON Inc.

U.S.A.
Tel: +1 805 964-6260
sales@teledyne-reson.com

Teledyne RESON U.K. Ltd.

Scotland U.K.
Tel: +44 1224 709 900
sales@reson.co.uk

Teledyne RESON B.V.

The Netherlands
Tel: +31 (0) 10 245 1500
info@reson.nl

Teledyne RESON GmbH

Germany
Tel: +49 421 3770 9600
info@teledyne-reson.com

Teledyne RESON Shanghai Office

Shanghai
Tel: +86 21 6110 8320
shanghai@teledyne-reson.com